DATA SHEET

Latest update
19-08-2026

Printed on:
02-11-2026

EARTHMAX SR 41



TIRE SIZE	**23.5 R 25**
UM	IS STANDARD
MACHINERY	DOZER / LOADER / ARTICULATED DUMP TRUCK (ADT) / LOW PROFILE DUMP TRUCK (LPDT)
VERSION	CUT RESISTANT COMPOUND
TL/TT	TL
LI/SS	185 B ; 195 A2

DIMENSIONS IS STANDARD

OW (MM)	615	**TRA CODE**	E4/L4
OD (MM)	1611	**STAR RATING**	★★/★
SLR (MM)	725	**TREAD DEPTH (MM)**	53
RC (MM)	4790	**TKPH (TK/H)**	161
RIM REC	19.50/2.5		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25
50	7500	7750	8250	8500	9000	9250
10	10300	10600	11200	11500	12150	--

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.